



DSU-2P

1 GHz 80 dB EMI MATV Power Passing Splitter



DSU-2P
(front view)

Features

- Broadband 5 to 1000 MHz frequency range
- High performance printed board circuitry provides improved hum modulation and intermodulation parameters to ensure superior signal quality
- Yellow-chromate plated zinc-alloy diecast housing ensures excellent ground bonding and long corrosion-free service life in indoor/outdoor applications
- Epoxy-sealed back cover provides effective EMI-RFI shielding > -80 dB, eliminating signal ingress to provide distortion-free pictures
- 1-inch centered 3/8" long precision machined F connector threads ensure improved port-to-connector interface and accommodate external security devices
- High retention seizing pins provide improved connectivity to connector center lead

Specifications

DSU-2P

MHz	INSERTION LOSS (Max. dB)	ISOLATION (Min. dB)	INPUT/OUTPUT RETURN LOSS (Min. dB)	RFI
5-400	3.6	20	18	> 80 dB
400-500	3.8	24	18	> 80 dB
470-600	4.0	23	18	> 80 dB
600-1000	4.0	20	18	> 80 dB

Ordering Information

Part Number	Description
DSU-2P	2-port 1 GHz Power Passing Splitter
DSU-3P	3-port 1 GHz Power Passing Splitter
DSU-4P	4-port 1 GHz Power Passing Splitter
DSU-8P	8-port 1 GHz Power Passing Splitter
MS-2D	2-port 1 GHz Power Passing Splitter

Products or features contained herein may be covered by one or more U.S. or foreign patents. Other non-ATX product and company names mentioned in this data sheet are the property of their respective companies.

© 2019 by ATX Networks Corp. and its affiliates (collectively "ATX Networks Corp."). All rights reserved. This material may not be published, broadcast, rewritten, or redistributed. Information in this document is subject to change without notice.
Rev. 10/19 (ANW1319)



ATX Networks

Tel: 289.204.7800 | Toll-Free: 866.YOUR.ATX | support@atx.com