

TSC Series

1GHz 130dB EMI Digital Directional Couplers/Taps



TSCW-9
(front view)

Features

- Digital-Ready Broadband 5 MHz to 1000 MHz frequency range
- TSC-SB series feature a solder-sealed back cover-plate to provide maximum EMI-RFI shielding >-130dB, eliminating signal ingress and distortion pictures
- High tap-to-output isolation provides spurious carrier protection and minimizes undesired channel interaction, reducing picture distortion
- High-performance printed board circuitry provides low intermodulation distortion to ensure excellent digital performance
- Capacitor coupling circuitry at all ports provide effective DC voltage blocking for improved hum modulation and intermodulation
- 1-inch centered 1/2" long precision machined F-connector threads ensure improved port-to-connector interface and accommodate external security devices

Ordering Information

PART NUMBER	DESCRIPTION
TSCW - (VALUES) SB	1 Wall Mount Directional Coupler (Values: 6, 9, 12, 16, 20, 24, 27, 30 dB)

Products or features contained herein may be covered by one or more U.S. or foreign patents. Other non-ATX product and company names mentioned in this data sheet are the property of their respective companies.

© 2019 by ATX Networks Corp. and its affiliates (collectively "ATX Networks Corp."). All rights reserved. This material may not be published, broadcast, rewritten, or redistributed. Information in this document is subject to change without notice.
Rev. 10/19 (ANW1355)



ATX Networks

Tel: 289.204.7800 | Toll-Free: 866.YOUR.ATX | support@atx.com