

LA-2150 Series

Satellite IF Inline Amplifiers



LA-2150
(front view)

Features

- High-grade satellite IF inline amplifiers suitable for DBS or MMDS applications
- Available in 950 to 2150 MHz for satellite only applications, or 40 to 2150 MHz for satellite and terrestrial applications
- 16 to 20 dB sloped versions compensate for loss on long cable runs
- DC pass through current 500 mA maximum for LNB powering
- Output level 45 dBmV maximum
- High performance SMD board circuitry
- Soldered back cover plate ensures high isolation > 120 dB
- Nickel plated zinc-alloy diecast housing

Specifications

LA-2150

BANDWIDTH	40-2150 MHz
GAIN	20 dB
NOISE FIGURE	5 dB
POWER INPUT	12-18 VDC
POWER REQUIRED	0.7W
WEIGHT	0.25 lbs (0.11 kg)

Ordering Information

Part Number	Description
LA-2150A	20 dB 40-2150 MHz Satellite IF Inline Amplifiers
LA-2150B	16-20 dB Sloped 40-2150 MHz Satellite IF Inline Amplifiers
LA-2150D	16-20 dB Sloped 950-2150 MHz Satellite IF Inline Amplifiers

Products or features contained herein may be covered by one or more U.S. or foreign patents. Other non-ATX product and company names mentioned in this data sheet are the property of their respective companies.

© 2019 by ATX Networks Corp. and its affiliates (collectively "ATX Networks Corp."). All rights reserved. This material may not be published, broadcast, rewritten, or redistributed. Information in this document is subject to change without notice.
Rev. 10/19 (ANW1322)



ATX Networks

Tel: 289.204.7800 | Toll-Free: 866.YOUR.ATX | support@atx.com