

Wolf Termination Bags can provide an airtight seal in innerduct diameters ranging from 2" to 5". The patented inflatable ADE/V sealing elements are made of a laminated foil developed for aircraft applications. The sealing element is placed in the duct around cables and inflated to the required air pressure via a durable metal air valve, completely sealing the innerduct. The sealing element may be easily removed by releasing the air pressure, again via the air valve. This allows incremental cable deployments and reduces your total installation cost.

The extremely low leakage rate of 2.7 mbarl/year ensures a service life of 20 years against gas diffusion, up to 16 feet water column (7 psi), and chemicals from pH2 to pH12.



## FEATURES

- Can be reused four (4) times
- Only two (2) components
- Simple, speedy installation and removal (even in confined spaces)
- Ready for immediate use and can be inflated with readily available inflation tools
- No damage to ducts and cables
- Independent of the number and outer diameter of cables installed
- Standard color: light blue

PART NUMBER	INNERDUCT DIAMETER	MINIMAL DUCT SEALING DIAMETER	OPTIMAL DUCT SEALING DIAMETER
MXCRTBVL50	2"	1.3"	0"
MXCRTBVL80	3"	2.2"	0"
MXCRTBVL100	4"	2.9"	0"
MXCRTBVL125	5"	3.5"	0.7"

Working temperature of +5°F to +86°F.

